

SNOL 67/350 LSN11

Economical low temperature oven SNOL 67/350 is designed for thermal treatment such as drying, heating, thermal testing, aging and similar purposes in natural air-flow environment up to 350°C. Good technical parameters ensure to high-quality results. This oven can be used in scientific laboratories, educational institutions, medicine and industry.

Basic model

- ✓ Control panel is placed on the left side,
- ✓ Natural air convection without air fan,
- ✓ 304 stainless steel chamber,
- ✓ 3 shelves,
- ✓ Outside casing – metal sheet, powder painted grey,
- ✓ Insulation rock wool (complete lack of asbestos),
- ✓ Door opening on the right, inner door in stainless steel, silicon joint,
- ✓ Microprocessor – temperature controller,
- ✓ Low electric power usage for increased energy efficiency,
- ✓ Short heating up / cooling down period,
- ✓ 1 year warranty.

Options

- ✓ Additional shelves
- ✓ Reinforced shelves
- ✓ Metal tray
- ✓ Digital timer for delayed start only
- ✓ Buzzer
- ✓ Over-temperature protection
- ✓ Data recorder
- ✓ Data communication/USB
- ✓ Calibration of temperature measurement system
- ✓ Oven exterior made from stainless steel
- ✓ Table for supporting the oven
- ✓ Additional 1 year warranty

Specifications

Technical data	SNOL 67/350 LSN11
Volume, L	67
Maximum temperature, °C	350
Continuous operating temperature, °C	T+10-350
Power	2
Rated supply voltage, V	230
Number of phases	1
Rated frequency, Hz	50
Chamber material	Mild steel
Maximum heating-up time (without charge), min.	40
Temperature stability	2
Temperature uniformity	14°C
Airflow	natural
Shelves (number)/max.	3/7
Chamber width, mm	390
Chamber depth, mm	445
Chamber height, mm	390
Overall width, mm	670
Overall depth, mm	615
Overall height, mm	580
Mass (Netto), kg	37

